



	DCV2012A	DCV2012B	DCV3016B	DCV4016B	DCV3021B	DCV3025B	DCV4021B	DCV4025B	DCV4035B
Table Size	2,000 x 1,100 mm 78.74" x 43.31"		3,260 x 1,500 mm 128.35" x 59.06"	4,260 x 1,500 mm 167.72" x 59.06"	3,100 x 2,000 mm 122.1" x 78.7"	3,100 x 2,400 mm 122.1" x 94.5"	4,100 x 2,000 mm 161.4" x 78.7"	4,100 x 2,400 mm 161.4" x 94.5"	4,100 x 2,400 mm 161.4" x 94.5"
X-axis Travel	2,000 mm 78.74"		3,060 mm 120.47"	4,065 mm 160.04"	3,060 mm 78.74"	3,060 mm 120.47"	4,065 mm 160.04"		
Y-axis Travel	1,200 mm 47.24"		1,600 mm 62.99"		2,100 mm 82.68"	2,500 mm 98.43"	2,100 mm 82.68"	2,500 mm 98.43"	3,500 mm 137.8"
Z-axis Travel (opt.)	600 mm 23.6"	762 mm 30"	762 mm (1,016mm) 30" (40")			762 mm 30" (1,016 mm 40")			
Spindle Speed (opt.)	20,000 rpm		10,000 rpm		4,500 rpm (6,000 / 10,000 rpm)		4,500 rpm (6,000 / 10,000 rpm)		
Spindle Taper (opt.)	BBT40		BBT50			BT50			
Max. Spindle Power	22kW 30 HP					22 kW 30 HP			
Tool Magazine Capacity (opt.)	24T (30T)	32T (40T)	40T (60T)		40T (60 / 120T)				
Machine Weight	16,000 kg 35,242 lb	21,000 kg 46,255 lb	31,000 kg 68,280 lb	35,000 kg 77,092 lb	43,000 kg 94,798 lb	47,000 kg 103,616 lb	45,000 kg 99,207 lb	49,000 kg 108,025 lb	55,000 kg 121,253 lb

1. The manufacturer reserves the right to modify the design, specifications, mechanisms, etc. to improve the performance of the machine without notice.  
All the specifications shown above are just for reference.
2. The appearance of the machines will be diverse due to different model and selectivity of accessories.