



	NFX380A	NFX500A
Table Size/ T-Slots	ø380 / 12 mm ø14.96" / 0.47"	ø500 / 14 mm ø19.7" / 0.55"
X-axis Travel	700 mm 27.56"	850 mm 33.5"
Y-axis Travel	520 mm 20.47"	762 mm 30"
Z-axis Travel	480 mm 18.9"	600 mm 23.6"
A-axis (Tilt)	150° (+30° / -120°)	
C-axis (Rotary)	360°	
A/C-axis Feed Rate	33.3 / 33.3 rev/min.	25 / 33.3 rpm
A/C Positioning Accuracy	10 / 10 sec.	
A/C Repeatability Accuracy	6 / 6 sec.	4 / 4 sec.
Spindle Speed (opt.)	12,000 rpm (15,000 rpm)	12,000 rpm (15,000 / 15,000 rpm)
Spindle Taper	BBT40	BBT40
Max. Spindle Power (opt.)	22 kW (22 kW) 30 HP (30 HP)	22 kW (22 / 30 kW) 30 HP (30 / 40 HP)
Tool Magazine Capacity	30T (40 / 60T)	48T (60T)
Machine Weight	6,210 kg 13,691 lb	11,000 kg 24,251 lb

1. The manufacturer reserves the right to modify the design, specifications, mechanisms, etc. to improve the performance of the machine without notice.
All the specifications shown above are just for reference.
2. The appearance of the machines will be diverse due to different model and selectivity of accessories.