



	NH 450A	NH 630B	NH 800B
Table Size	400 x 400 mm (500 x 500 mm) 15.75" x 15.75" (19.69" x 19.69")	630 x 630 mm 24.8" x 24.8"	800 x 800 mm 31.5" x 31.5"
X-axis Travel	640 mm 25.2"	1,050 mm 41.34"	1,300 mm 51.18"
Y-axis Travel	610 mm 24.02"	850 mm 33.46"	1,100 mm 43.31"
Z-axis Travel	680 mm 26.77"	850 mm 33.46"	1,100 mm 43.31"
Spindle Speed	15,000 rpm	10,000 rpm (8,000 rpm)	10,000 rpm (8,000 rpm)
Spindle Taper	BBT40	BBT50	BBT50
Max. Spindle Power (opt.)	22 kW 30 HP	45 kW (55 kW) 60 HP (74 HP)	45 kW (55 kW) 60 HP (74 HP)
Tool Magazine Capacity (opt.)	40T (60T)	40T (60T / 120T)	40T (60T / 120T)
Machine Weight	10,945 kg 24,129 lb	26,000 kg 57,320 lb (26,500 / 27,000 kg) (58,422 / 59,524 lb)	26,000 kg 57,320 lb (26,500 / 28,500 kg) (58,422 / 62,831 lb)

1. The manufacturer reserves the right to modify the design, specifications, mechanisms, etc. to improve the performance of the machine without notice.  
All the specifications shown above are just for reference.
2. The appearance of the machines will be diverse due to different model and selectivity of accessories.